



Excellent Colour Last

As a result of extensive research in our high-tech laboratories, Jotun's unique *TrueColour Technology* enables **Gardex** colours to stand the test of time. This will maintain the beauty of your property for a longer period.



Anti Rust

Gardex ensures protection against rusting that will corrode metal substrates. It enhances the strength and beauty of metal surfaces for years to come.



100% free from Heavy Metals

At Jotun, we maintain the highest standards of health, safety and environment. **Gardex** is formulated without any lead and mercury to ensure the product is safe for you and your family.



to ensure a smooth and tough finish. This formula emphasizes proper drying on the top and bottom layer of each coat, resulting in a high quality finish.



Gardex prevents harmful fungus that will cause wood to rot and also avoid harm to your well-being.



Gardex offers the widest range of colours tailored to your preference and to match your home. Choose colours from our inspiring colour themes or create your own colours limited only



Optimized Drying Time

Gardex formulation has its drying time optimized



Anti Fungal

Multicolor Tintable

by your imagination.

PRODUCT FEATURES

	Low Odour	Optimized Drying Time	Excellent Colour Last	Weather Resistance	Anti Fungal and Anti Rust	100% free from Heavy Metals	Finishing
GARDEX Premium Gloss GARDEX PREMIUM GLOSS PREMIUM GLOSS	***	***	***	***	***	***	Gloss & Semi Gloss
JOTAGLOSS JOTUN JOTAGLOSS Walt Law Law JOTAGLOSS JOTUN JOTAGLOSS JOTA	*	***	**	***	*	***	Gloss

★★★ Excellent ★★ Very Good ★ Good

RECOMMENDED PAINT SYSTEM



Coverage

Thinning

Application

Fast drying primer with very low odour to provide excellent adhesion between the substrate and the topcoat. Specially formulated with Anti Rust agents for superior protection against rust.

SURFACE PREPARATION

On chalky and dusty surfaces, all loose materials must be removed before painting. For wood surface, sand paper should be used to remove loose materials. For metal surface, a scraper can be used to remove flaking, rust and old paint. Clean the surface with water and/or soap with a brush or cloth and allow surface to dry before painting. 14m²/litre Drying Time 2 - 4 hours **Recoating Time** 8 - 12 hours Dilution is not necessary. If required, dilute with Jotun Thinner No.2 (max 5%)

Colour your imagination with

Jotun ColourAdvisor

Brush, roller or spray

To find out more, log on to jotun.com/ap







Clean brushes and tools with Jotun Thinner No.2

JOTUN





GARDEX

—PREMIUM GLOSS—

WOOD & METAL



Low Odour

JOTUN

GARDEX

By using Low Aromatic Formulation, **Gardex** ensures less smell during and after application. You and your family can immediately move into your newly painted home without having to suffer from the unpleasant paint odour anymore!





